



Pearson
Edexcel

Mark Scheme (Results)

October 2019

Pearson Edexcel International Advanced
Level

In Physics (WPH06)

Paper 01 Experimental Physics

Edexcel and BTEC Qualifications

Edexcel and BTEC qualifications come from Pearson, the world's leading learning company. We provide a wide range of qualifications including academic, vocational, occupational and specific programmes for employers. For further information, please visit our website at www.edexcel.com

Our website subject pages hold useful resources, support material and live feeds from our subject advisors giving you access to a portal of information. If you have any subject specific questions about this specification that require the help of a subject specialist, you may find our Ask The Expert email service helpful.

www.edexcel.com/contactus

Pearson: helping people progress, everywhere

Our aim is to help everyone progress in their lives through education. We believe in every kind of learning, for all kinds of people, wherever they are in the world. We've been involved in education for over 150 years, and by working across 70 countries, in 100 languages, we have built an international reputation for our commitment to high standards and raising achievement through innovation in education. Find out more about how we can help you and your students at:

www.pearson.com/uk

October 2019

Publications Code WPH06_01_1910_MS

All the material in this publication is copyright

© Pearson Education Ltd 2019

General Marking Guidance

- All candidates must receive the same treatment. Examiners must mark the first candidate in exactly the same way as they mark the last.
- Mark schemes should be applied positively. Candidates must be rewarded for what they have shown they can do rather than penalised for omissions.
- Examiners should mark according to the mark scheme not according to their perception of where the grade boundaries may lie.
- There is no ceiling on achievement. All marks on the mark scheme should be used appropriately.
- All the marks on the mark scheme are designed to be awarded. Examiners should always award full marks if deserved, i.e. if the answer matches the mark scheme. Examiners should also be prepared to award zero marks if the candidate's response is not worthy of credit according to the mark scheme.
- Where some judgement is required, mark schemes will provide the principles by which marks will be awarded and exemplification may be limited.
- When examiners are in doubt regarding the application of the mark scheme to a candidate's response, the team leader must be consulted.
- Crossed out work should be marked UNLESS the candidate has replaced it with an alternative response.

Mark scheme notes

Underlying principle

The mark scheme will clearly indicate the concept that is being rewarded, backed up by examples. It is not a set of model answers.

For example:

(iii) Horizontal force of hinge on table top

66.3 (N) or 66 (N) **and** correct indication of direction [no ue]

✓ 1

[Some examples of direction: acting from right (to left) / to the left / West / opposite direction to horizontal. May show direction by arrow.

Do not accept a minus sign in front of number as direction.]

This has a clear statement of the principle of awarding the mark, supported by some examples illustrating acceptable boundaries.

1. Mark scheme format

- 1.1 You will not see 'wtte' (words to that effect). Alternative correct wording should be credited in every answer unless the ms has the specific words that must be present. Such words will be indicated by underlining, e.g. 'resonance'.
- 1.2 Bold lower case will be used for emphasis.
- 1.3 Round brackets () indicate words that are not essential, e.g. "(hence) distance is increased".
- 1.4 Square brackets [] indicate advise to examiners or examples, e.g. [Do not accept gravity] [ecf].

2. Unit error penalties

- 2.1 A separate mark is not usually given for a unit but a missing or incorrect unit will normally cause the final calculation mark to be lost.
- 2.2 Incorrect use of case, e.g. 'Watt' or 'w' will not be penalised.
- 2.3 There will be no unit error penalty applied in 'show that' questions or in any other question where the units to be used have been given.
- 2.4 The same missing or incorrect unit will not be penalised more than once within a question.
- 2.5 Occasionally, it may be decided not to penalise a missing or incorrect unit, e.g. the candidate may be calculating the gradient of a graph, resulting in a unit that is not one that should be known and is complex.
- 2.6 The mark scheme will indicate if no unit error penalty is to be applied by means of [no ue].

3. Significant figures

Use of an inappropriate number of significant figures in the theory papers will normally only be penalised in 'show that' questions where use of too few significant figures has resulted in the candidate not demonstrating the validity of the given answer.

4. Calculations

- 4.1 Bald (i.e. no working shown) correct answers score full marks unless in a 'show that' question.
- 4.2 If a 'show that' question is worth 2 marks then both marks will be available for a reverse working; if it is worth 3 marks then only 2 will be available.
- 4.3 Use of the formula means that the candidate demonstrates substitution of physically correct values, although there may be conversion errors, e.g. power of 10 error.
- 4.4 Recall of the correct formula will be awarded when the formula is seen or implied by substitution.
- 4.5 The mark scheme will show a correctly worked answer for illustration only.
- 4.6 Example of mark scheme for a calculation:

'Show that' calculation of weight

Use of $L \times W \times H$ ✓

Substitution into density equation with a volume and density ✓

Correct answer [49.4 (N) to at least 3 sig fig. [No ue] ✓

[If 5040 g rounded to 5000 g or 5 kg, do not give the 3rd mark; if conversion to kg is omitted then the answer is fudged, do not give 3rd mark.]

[Bald answer scores 0, reverse calculation 2/3]

Example of answer:

$$80 \text{ cm} \times 50 \text{ cm} \times 1.8 \text{ cm} = 7200 \text{ cm}^3$$

$$7200 \text{ cm}^3 \times 0.70 \text{ g cm}^{-3} = 5040 \text{ g}$$

$$5040 \times 10^{-3} \text{ kg} \times 9.81 \text{ N/kg}$$

$$= 49.4 \text{ N}$$

5. Quality of Written Communication

- 5.1 Indicated by QoWC in mark scheme. QWC – Work must be clear and organised in a logical manner using technical wording where appropriate.
- 5.2 Usually it is part of the max mark.


6. Graphs

- 6.1 A mark for axes requires both axes to be labelled with quantities and units, and drawn the correct way round.

- 6.2 Sometimes a separate mark will be given for units or for each axis if the units are complex. This will be indicated on the mark scheme.
- 6.3 A mark given for choosing a scale requires that the chosen scale allows all points to be plotted, spreads plotted points over more than half of each axis and is not an awkward scale, e.g. multiples of 3, 7 etc.
- 6.4 Points should be plotted to within 1 mm.
- Check the two furthest from the best line. If both OK award mark.
 - If either is 2 mm out do not award mark.
 - If both are 1 mm out do not award mark.
 - If either is 1 mm out then check another two and award mark if both of these are OK, otherwise no mark.
- 6.5 For a line mark there must be a thin continuous line that is the best-fit line for the candidate's results.

Question Number	Answer	Mark								
1(a)(i)	(A larger distance will) reduce the percentage uncertainty (1) Accept %U, % uncertainty, not uncertainty/ error. Accept words that imply reduce but not eliminate.	(1)								
1(a)(ii)	Any ONE from: Repeat at different places and calculate a mean (1) to reduce (the effect of) random errors (1) OR Check for zero error (on the micrometer) (1) to eliminate systematic error (1) OR Use the ratchet (1) to avoid squashing the metal Or to reduce (the effect of) random (1) errors OR Squeeze to remove air gaps (1) to eliminate systematic error (1) OR Take measurements away from the folded edge (1) as the fold will be thicker Or to reduce (the effect of) random (1) errors MP2 is dependent on MP1	(2)								
1(b)(i)	Units consistent with readings in mm (1) Values listed as 0.47, 0.49, 0.47, 0.48 (accept any order, 2 sf) (1) <u>Example</u> <table border="1" data-bbox="320 1619 1190 1704"> <thead> <tr> <th colspan="4">total thickness / mm</th> </tr> </thead> <tbody> <tr> <td>0.47</td> <td>0.49</td> <td>0.47</td> <td>0.48</td> </tr> </tbody> </table>	total thickness / mm				0.47	0.49	0.47	0.48	(2)
total thickness / mm										
0.47	0.49	0.47	0.48							
1(b)(ii)	Correct mean to 2 sf (1) Correct absolute uncertainty using half range (accept 1, 2 or (1) 3 sf) Allow e.c.f. from 1(b)(i) for both marks <u>Example of calculation</u>									

	<p>Mean thickness = $(0.47 + 0.49 + 0.47 + 0.48) \text{ mm} / 4 = 0.48 \text{ mm}$ Half range = $(0.49 - 0.47) / 2 = 0.01 \text{ mm}$</p>		(2)
1(c)(i)	<p>Use of $\rho = m/V$ (1) 2700 (kg m^{-3}) (accept 2680) (1)</p> <p>Allow ecf from (b)(ii)</p> <p><u>Example of calculation</u></p> $\rho = \frac{3.62 \times 10^{-3} \text{ kg}}{0.30 \text{ m} \times 0.30 \text{ m} \times (0.48 \times 10^{-3}) \text{ m} / 32} = 3.62 \times 10^{-3} \text{ kg} / 1.35 \times 10^{-6} \text{ m}^3 = 2680 \text{ kg m}^{-3}$		(2)
1(c)(ii)	<p>Correct calculation of percentage uncertainty in ρ shown (1) (allow ecf from (b)(ii)) (1) Correct upper and/or lower limit based on calculated percentage uncertainty (allow ecf from (c)(i)) (1) Valid conclusion based on comparison of given density with calculated limit (dependent on MP2)</p> <p><u>Example of calculation</u></p> <p>$\%U = (2 \times 0.1/30 + 0.01/0.48 + 0.01/3.62) \times 100\% = 0.67\% + 2.1\% + 0.28\% = 3.1\%$ Upper limit = $2700 \text{ kg m}^{-3} \times 103.1\% = 2780 \text{ kg m}^{-3}$ The quoted value falls within the limits therefore the metal could be aluminium (1) (1)</p> <p>Or (1)</p> <p>Correct calculation of percentage uncertainty in ρ shown (allow ecf from (b)(ii)) Correct calculation percentage difference shown (allow ecf from (c)(i)) Valid conclusion based on comparison of correct percentage difference and calculated percentage uncertainty (dependent on MP2)</p> <p><u>Example of calculation</u></p> <p>$\%U = (2 \times 0.1/30 + 0.01/0.48 + 0.01/3.62) \times 100\% = 0.67\% + 2.1\% + 0.28\% = 3.1\%$ $\%D = (2700 - 2710)/2710 \times 100\% = 0.37\%$ $\%D$ is less than $\%U$ therefore the metal could be aluminium</p>		(3)
Total for Question 1			12

Question Number	Answer	Mark
2 (a) (i)	<p>Tangent drawn at $\theta = 70.0\text{ }^{\circ}\text{C}$ (1)</p> <p>Gradient in range -2.80 to $-3.10\text{ }(^{\circ}\text{C min}^{-1})$ to 2 or 3 sf (1)</p> <p>calculated from the tangent drawn (Allow -4.67×10^{-2} to $-5.17 \times 10^{-2}\text{ }^{\circ}\text{C s}^{-1}$)</p> <p><u>Example of calculation</u></p>  <p>$\Delta\theta / \Delta t = (62.0 - 77.8) / 5.4 = -2.93\text{ }^{\circ}\text{C min}^{-1}$</p>	(2)
2(a)(ii)	<p>Use of $\Delta E / \Delta t = mc \times \Delta\theta / \Delta t$ (1)</p> <p>$\Delta E / \Delta t = 1180$ to 1300 J min^{-1} (20 to 22 W) to 2 or 3 sf (1)</p> <p>(allow ecf (a)(i))</p> <p><u>Example of calculation</u></p> <p>$\Delta E / \Delta t = 100\text{ cm}^3 \times 1.0\text{ g cm}^{-3} \times 4.2\text{ J g}^{-1}\text{K}^{-1} \times 2.93\text{ }^{\circ}\text{C min}^{-1}$ $= 1230\text{ J min}^{-1}$</p>	(2)
2(b)(i)	<p>Volume/mass (1)</p> <p>Or</p> <p>Temperature of the surroundings (1)</p> <p>Or</p> <p>Initial temperature of water (1)</p>	(1)

2(b)(ii)	Compare the gradient Or rate of change of temperature Or rate of energy transfer At the same temperature/time Or Compare the time taken For the same change in temperature Or Compare the temperature change Over the same time interval	(1) (1) (1) (1) (1) (1)	(2)
2(b)(iii)	Difficult to ensure temperature of surroundings remains constant So repeat readings are not appropriate MP2 dependent on MP1	(1) (1)	(2)
Total for Question 2			9

Question Number	Answer	Mark	
3 (a)	Zero the top pan balance without the top magnet Or measure the mass of a single magnet Measure x using a metre rule Or vernier calipers Vary x and record the corresponding balance readings	(1) (1) (1)	(3)
3 (b)	Multiply the balance readings by g to obtain F Or state balance readings are proportional to F Plot a graph of $\log F$ against $\log x$ Or $\ln F$ against $\ln x$ To check it is a straight line Or to check it has a constant gradient 3a and 3b to be marked holistically	(1) (1) (1)	(3)
Total for Question 3			6

Question Number	Answer	Mark
4 (a)	Energy is (permanently) removed/dissipated (from the system) Or energy is lost from the system (1)	(2)
	Resulting in a decrease in amplitude (1)	
4 (b)	$\ln A = \ln A_0 - \lambda n$ (1) is in the form $y = c + mx$ where $-\lambda$ is the gradient (which is constant) (1)	(2)
	MP2 dependent on MP1	
4 (c)(i)	$\ln A$ values correct to 3 or 4 sf (1)	(5)
	Axes labelled: y as $\ln(A/\text{cm})$ and x as n (1)	
	Suitable scales for $\ln(A/\text{cm})$ and x as n (1)	
	Processed data plotted accurately to $\pm 1\text{mm}$ (1)	
	Line of best fit (1)	
4 (c)(ii)	Calculation of gradient using a large triangle shown (1)	(2)
	Correct value of λ to 2 or 3 sf, no unit, positive (1)	
4 (d)	High sampling rate near the maximum displacement (1)	(2)
	Parallax error at the maximum displacement is eliminated (1)	
Total for Question 4		13

